

| | |
|--|--|
| Side Shifting Rotary Tillers | |
| Side Shifting Rotary Tiller with Hydraulic Sensing Device | |
| | |
| | |
| Technical Specifications | |

| TECHNICAL SPECIFICATIONS | T-HDR 1600 | T-HDR 1850 | T-HDR 2100 |
|---------------------------------|-------------------|-------------------|-------------------|
| Work Width (mm) | 1514 | 1768 | 2022 |
| Working Depth (mm) | 220 | | |
| Overall Width (mm) | 1750 | 1985 | 2220 |
| Overall Length (mm) | 1050 | | |
| Overall Height (mm) | 1150 | | |
| Number of Flanges | 7 (6 opt.) | 8 (7 opt.) | 9 (8 opt.) |
| Number of Blades | 36 | 42 | 48 |
| Machine Weight (kg) | 520 | 570 | 600 |
| PTO Shaft RPM (min-1) | 540 | | |
| Required Power (HP) | 40-45 | 45-50 | 50-55 |

| | |
|------------------------------------|--|
| Side Shifting Rotary Tiller | |
| | |
| | |
| | |
| Technical Specifications | |

| TECHNICAL SPECIFICATIONS | T-HKR 1600 | T-HKR 1850 | T-HKR 2100 | T-HKR 2400 | T-HKDDR 1600 | T-HKDDR 1850 | T-HKDDR 2100 | T-HKDDR 2400 |
|---------------------------------|-------------------|-------------------|-------------------|-------------------|---------------------|---------------------|---------------------|---------------------|
| Work Width (mm) | 1514 | 1768 | 2022 | 2235 | 1514 | 1768 | 2022 | 2235 |
| Working Depth (mm) | 220 | | | | | | | |
| Overall Width (mm) | 1740 | 1975 | 2210 | 2480 | 1740 | 1975 | 2210 | 2480 |
| Overall Length (mm) | 1050 | | | | | | | |
| Overall Height (mm) | 1150 | | | | 1200 | | | |
| Number of Flanges | 7 (6 opt.) | 8 (7 opt.) | 9 (8 opt.) | 10 (9 opt.) | 7 (6 opt.) | 8 (7 opt.) | 9 (8 opt.) | 10 (9 opt.) |
| Number of Blades | 36 | 42 | 48 | 54 | 36 | 42 | 48 | 54 |
| Machine Weight (kg) | 485 | 510 | 535 | 580 | 500 | 570 | 640 | 718 |
| PTO Shaft RPM (min-1) | 540 | | | | 540 | | | |
| Required Power (HP) | 35-40 | 40-45 | 45-50 | 50-55 | 40-45 | 45-50 | 50-55 | 60-65 |

| | |
|---|--|
| Mechanical Side Shifting Rotary Tiller | |
|---|--|

| | |
|---------------------------------|--|
| | |
| | |
| | |
| Technical Specifications | |

| TECHNICAL SPECIFICATIONS | T-MKR 1400 | T-MKR 1600 | T-MKR 1850 | T-MKR 2100 |
|---------------------------------|-------------------|-------------------|-------------------|-------------------|
| Work Width (mm) | 1260 | 1514 | 1768 | 2022 |
| Working Depth (mm) | 220 | | | |
| Overall Width (mm) | 1516 | 1770 | 2024 | 2278 |
| Overall Length (mm) | 850 | | | |
| Overall Height (mm) | 1050 | | | |
| Number of Flanges | 6 (5 opt.) | 7 (6 opt.) | 8 (7 opt.) | 9 (8 opt.) |
| Number of Horizontal Blades | 30 | 36 | 42 | 48 |
| Number of Vertical Blades | 36 | 44 | 52 | 60 |
| Machine Weight (kg) | 395 | 415 | 450 | 480 |
| PTO Shaft RPM (min-1) | 54 | | 0 | |
| Required Power (HP) | 30-35 | 35-40 | 40-45 | 45-50 |